



**卫生级离心泵** Sanitary centrifugal pump

- 连接方式:快装式、螺纹式 Connection mode:welded,quick-install, threaded
- 材质:SUS304、SUS316L Materials:SUS304、SUS316L
- 密封方式:机械密封 Seal mode:mechanical seal
- 应用于各种不锈钢管道领域 Apply for every kinds of stainless steel pipeline



**卫生级离心泵** Sanitary centrifugal pump

- 连接方式:快装式、螺纹式 Connection mode:welded,quick-install, threaded
- 材质:SUS304、SUS316L Materials:SUS304、SUS316L
- 密封方式:机械密封 Seal mode:mechanical seal
- 应用于各种不锈钢管道领域 Apply for every kinds of stainless steel pipeline

型号 Model	流量(吨/小时) Flow(Ton/h)	扬程 (米水柱) Delivery lift	电机功率 Motor power	进出口径 Inlet/outlet diameters	备注 Remarks
WXH-15-14	1.5	14	0.55	38/25	配ABB电机
WXH-3-14	3	14	1.1	38/38	配ABB电机
WXH-5-24	5	24	1.5	50/38	配ABB电机
WXH-5-30	5	30	2.2	50/38	配ABB电机
WXH-10-24	10	24	2.2	50/38	配ABB电机
WXH-10-36	10	36	3	50/38	配ABB电机
WXH-15-24	15	24	3	50/50	配ABB电机
WXH-20-24	20	24	4	50/50	配ABB电机
WXH-20-36	20	36	5.5	65/50	配ABB电机
WXH-30-24	30	24	5.5	65/50	配ABB电机
WXH-30-36	30	36	7.5	65/50	配ABB电机
WXH-40-36	40	36	11	80/65	配ABB电机
WXH-80-30	80	30	15	100/85	配ABB电机
WXH-80-40	80	40	18.5	100/85	配ABB电机